

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 September 2001 (07.09.2001)

PCT

(10) International Publication Number  
WO 01/65066 A1

(51) International Patent Classification<sup>7</sup>: E21B 47/12

(21) International Application Number: PCT/US01/06907

(22) International Filing Date: 2 March 2001 (02.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/186,503 2 March 2000 (02.03.2000) US

(71) Applicant (for all designated States except US): SHELL  
OIL COMPANY [US/US]; One Shell Plaza, P.O. Box  
2463, Houston, TX 77252-2463 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VINEGAR,


Harold, J. [US/US]; 5219 Yarwell, Houston, TX 77096  
(US). BURNETT, Robert, Rex [US/US]; 20711 Flag-  
more Court, Katy, TX 77450 (US). SAVAGE, William,  
Mountjoy [US/US]; 8446 Ariel, Houston, TX 77074  
(US). CARL, Frederick, Gordon, Jr. [US/US]; 8406  
Edgemoor, Houston, TX 77036 (US). BERCHENKO,  
Ilya, Emil [RU/US]; 2102 Pine Drive, Friendswood, TX  
77546 (US).

(74) Agent: CHRISTENSEN, Del, S.; Shell Oil Company,  
One Shell Plaza, P.O. Box 2463, Houston, TX 77252-2463  
(US).

(81) Designated States (national): AE, AG, AI, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,  
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,  
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,  
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,  
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: WIRELESS COMMUNICATION USING WELL CASING



(57) Abstract: A petroleum well having a borehole extending into a formation is provided. A piping structure is positioned within the borehole, and an induction choke is positioned around the piping structure downhole. A communication system is provided along the piping structure between a surface of the well and the induction choke. A downhole module is positioned on an exterior surface of the piping structure and is configured to measure characteristics of the formation. The formation characteristics, such as pressure and resistivity, are communicated to the surface of the well along the piping structure.

Best Available Copy

WO 01/65066 A1



**(84) Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## WIRELESS COMMUNICATION USING WELL CASING

## CROSS-REFERENCES TO RELATED APPLICATIONS

- 10 This application claims the benefit of the following U.S. Provisional Applications, all of which are hereby incorporated by reference:

COMMONLY OWNED AND PREVIOUSLY FILED U.S. PROVISIONAL PATENT APPLICATIONS			
T&K #	Serial Number	Title	Filing Date
TH 1599	60/177,999	Toroidal Choke Inductor for Wireless Communication and Control	Jan. 24, 2000
TH 1600	60/178,000	Ferromagnetic Choke in Wellhead	Jan. 24, 2000
TH 1602	60/178,001	Controllable Gas-Lift Well and Valve	Jan. 24, 2000
TH 1603	60/177,883	Permanent, Downhole, Wireless, Two-Way Telemetry Backbone Using Redundant Repeater, Spread Spectrum Arrays	Jan. 24, 2000
TH 1668	60/177,998	Petroleum Well Having Downhole Sensors, Communication, and Power	Jan. 24, 2000
TH 1669	60/177,997	System and Method for Fluid Flow Optimization	Jan. 24, 2000
TS.6185	60/181,322	A Method and Apparatus for the Optimal Predistortion of an Electromagnetic Signal in a Downhole Communications System	Feb. 9, 2000
TH 1599x	60/186,376	Toroidal Choke Inductor for Wireless Communication and Control	Mar. 2, 2000
TH 1600x	60/186,380	Ferromagnetic Choke in Wellhead	Mar. 2, 2000
TH 1601	60/186,505	Reservoir Production Control from Intelligent Well Data	Mar. 2, 2000
TH 1671	60/186,504	Tracer Injection in a Production Well	Mar. 2, 2000
TH 1672	60/186,379	Oilwell Casing Electrical Power Pick-Off Points	Mar. 2, 2000
TH 1673	60/186,394	Controllable Production Well Packer	Mar. 2, 2000
TH 1674	60/186,382	Use of Downhole High Pressure Gas in a Gas Lift Well	Mar. 2, 2000
TH 1675	60/186,503	Wireless Smart Well Casing	Mar. 2, 2000
TH 1677	60/186,527	Method for Downhole Power Management Using Energization from Distributed Batteries or Capacitors with Reconfigurable Discharge	Mar. 2, 2000

TH 1679	60/186,393	Wireless Downhole Well Interval Inflow and Injection Control	Mar. 2, 2000
TH 1681	60/186,394	Focused Through-Casing Resistivity Measurement	Mar. 2, 2000
TH 1704	60/186,531	Downhole Rotary Hydraulic Pressure for Valve Actuation	Mar. 2, 2000
TH 1705	60/186,377	Wireless Downhole Measurement and Control For Optimizing Gas Lift Well and Field Performance	Mar. 2, 2000
TH 1722	60/186,381	Controlled Downhole Chemical Injection	Mar. 2, 2000
TH 1723	60/186,378	Wireless Power and Communications Cross-Bar Switch	Mar. 2, 2000

5

The current application shares some specification and figures with the following commonly owned and concurrently filed applications, all of which are hereby incorporated by reference:

COMMONLY OWNED AND CONCURRENTLY FILED U.S. PATENT APPLICATIONS			
T&K #	Serial Number	Title	Filing Date
TH 1601US	09/_____	Reservoir Production Control from Intelligent Well Data	
TH 1671US	09/_____	Tracer Injection in a Production Well	
TH 1672US	09/_____	Oil Well Casing Electrical Power Pick-Off Points	
TH 1673US	09/_____	Controllable Production Well Packer	
TH 1674US	09/_____	Use of Downhole High Pressure Gas in a Gas-Lift Well	
TH 1677US	09/_____	Method for Downhole Power Management Using Energization from Distributed Batteries or Capacitors with Reconfigurable Discharge	
TH 1679US	09/_____	Wireless Downhole Well Interval Inflow and Injection Control	
TH 1681US	09/_____	Focused Through-Casing Resistivity Measurement	
TH 1704US	09/_____	Downhole Rotary Hydraulic Pressure for Valve Actuation	
TH 1705US	09/_____	Wireless Downhole Measurement and Control For Optimizing Gas Lift Well and Field Performance	
TH 1722US	09/_____	Controlled Downhole Chemical Injection	
TH 1723US	09/_____	Wireless Power and Communications Cross-Bar Switch	

- 5 The current application shares some specification and figures with the following commonly owned and previously filed applications, all of which are hereby incorporated by reference:

COMMONLY OWNED AND PREVIOUSLY FILED U.S PATENT APPLICATIONS			
T&K #	Serial Number	Title	Filing Date
TH 1599US	09/ _____	Choke Inductor for Wireless Communication and Control	
TH 1600US	09/ _____	Induction Choke for Power Distribution in Piping Structure	
TH 1602US	09/ _____	Controllable Gas-Lift Well and Valve	
TH 1603US	09/ _____	Permanent Downhole, Wireless, Two-Way Telemetry Backbone Using Redundant Repeater	
TH 1668US	09/ _____	Petroleum Well Having Downhole Sensors, Communication, and Power	
TH 1669US	09/ _____	System and Method for Fluid Flow Optimization	
TH 1783US	09/ _____	Downhole Motorized Flow Control Valve	
TS 6185US	09/ _____	A Method and Apparatus for the Optimal Predistortion of an Electro Magnetic Signal in a Downhole Communications System	

- The benefit of 35 U.S.C. § 120 is claimed for all of the above referenced commonly owned applications. The applications referenced in the tables above are referred to herein as the “Related Applications.”

## BACKGROUND OF THE INVENTION

### Field of the Invention

- 15 The present invention relates in general to petroleum wells, and in particular to a petroleum well having a casing which is used as a conductive path to transmit wireless spread spectrum communications between surface equipment and a downhole module used to measure physical characteristics of a petroleum formation or condition of well structures.

### 20 Description of Related Art

Several methods have been devised to place electronics, sensors, or controllable valves downhole along an oil production tubing string, but all such known devices typically use an

5 internal or external cable along the tubing string to provide power and communications downhole. It is, of course, highly undesirable and in practice difficult to use a cable along the tubing string either integral to the tubing string or spaced in the annulus between the tubing string and the casing. The use of a cable presents difficulties for well operators while assembling and inserting the tubing string into a borehole. Additionally, the cable is subjected  
10 to corrosion and heavy wear due to movement of the tubing string within the borehole. An example of a downhole communication system using a cable is shown in PCT/EP97/01621.

U. S. Patent No. 4,839,644 describes a method and system for wireless two-way communications in a cased borehole having a tubing string. However, this system describes a communication scheme for coupling electromagnetic energy in a TEM mode using the annulus  
15 between the casing and the tubing. This inductive coupling requires a substantially nonconductive fluid such as crude oil in the annulus between the casing and the tubing. Therefore, the invention described in U. S. Patent No. 4,839,644 has not been widely adopted as a practical scheme for downhole two-way communication. Another system for downhole communication using mud pulse telemetry is described in U. S. Patent Nos. 4,648,471 and  
20 5,887,657. Although mud pulse telemetry can be successful at low data rates, it is of limited usefulness where high data rates are required or where it is undesirable to have complex, mud pulse telemetry equipment downhole. Other methods of communicating within a borehole are described in U.S. Patent Nos. 4,468,665; 4,578,675; 4,739,325; 5,130,706; 5,467,083; 5,493,288; 5,576,703; 5,574,374; and 5,883,516. Similarly, several permanent downhole  
25 sensors and control systems have been described in U.S. Pat. Nos. 4,972,704; 5,001,675; 5,134,285; 5,278,758; 5,662,165; 5,730,219; 5,934,371; and 5,941,307.

Due to the limited success of wireless communication within a borehole, the current use of downhole measurement and control equipment is minimal. A lack of downhole measurement and control restricts the ability to maximize economic return by optimizing production of the  
30 well.

It would, therefore, be a significant advance in the operation of petroleum wells if an alternate means for providing communications within a well were provided. More specifically, it would be advantageous if downhole physical characteristics of the formation could be easily communicated to the surface of the well. This information could then be used to increase the  
35 aggregate recovery of formation reserves, and would thereby optimize production of the well.

All references cited herein are incorporated by reference to the maximum extent allowable by law. To the extent a reference may not be fully incorporated herein, it is

5 incorporated by reference for background purposes and indicative of the knowledge of one of ordinary skill in the art.

### BRIEF SUMMARY OF THE INVENTION

The problems associated with communicating in the borehole of a petroleum well are  
10 solved by the present invention. The metal well casing is used as a power and communications path between the surface and downhole modules, with a formation ground used as the return path to complete the electrical circuit. Communications are implemented using spread-spectrum transceivers at the wellhead and at the downhole modules. The communications enable transmission of measurements from downhole sensors to the surface and control of downhole  
15 devices.

A petroleum well according to the present invention includes a downhole module and a communications system. The downhole module is positioned on an exterior surface of a piping structure, the piping structure being positioned within a borehole of the petroleum well that extends into a formation. The downhole module collects formation data from the formation and  
20 communicates the data by using the communication system. The signals transmitted by the communication system are passed along the piping structure.

A method for assessing a formation according to the present invention is applied to a petroleum well having a borehole that extends into the formation. The petroleum well also includes a piping structure that is positioned within the borehole. The method includes the step  
25 of sensing a formation characteristic within the formation and then communicating information about the formation characteristic along the piping structure of the well.

A downhole module according to the present invention is adapted for coupling to a piping structure of a petroleum well. The module includes a sensor that is used to sense a physical characteristic of a formation surrounding the piping structure. A downhole modem is  
30 used to transmit data representing the physical characteristic along the piping structure of the well.

### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1A is a schematic of a petroleum well having a downhole module attached to a casing, the downhole module being configured to measure formation characteristics according to  
35 the present invention.

5

**DESCRIPTION OF THE PREFERRED EMBODIMENTS**

As used in the present application, a "piping structure" can be one single pipe, a tubing string, a well casing, a pumping rod, a series of interconnected pipes, rods, rails, trusses, lattices, supports, a branch or lateral extension of a well, a network of interconnected pipes, or other structures known to one of ordinary skill in the art. The preferred embodiment makes use of the invention in the context of an oil well where the piping structure comprises tubular, metallic, electrically-conductive pipe or tubing strings, but the invention is not so limited. For the present invention, at least a portion of the piping structure needs to be electrically conductive, such electrically conductive portion may be the entire piping structure (e.g., steel pipes, copper pipes) or a longitudinal extending electrically conductive portion combined with a longitudinally extending non-conductive portion. In other words, an electrically conductive piping structure is one that provides an electrical conducting path from one location where a power source is electrically connected to another location where a device and/or electrical return is electrically connected. The piping structure will typically be conventional round metal tubing, but the cross-sectional geometry of the piping structure, or any portion thereof, can vary in shape (e.g., round, rectangular, square, oval) and size (e.g., length, diameter, wall thickness) along any portion of the piping structure.

A "valve" is any device that functions to regulate the flow of a fluid. Examples of valves include, but are not limited to, sub-surface safety valves used to control fluid flow in well tubulars, and bellows-type gas-lift valves and controllable gas-lift valves each of which may be used to regulate the flow of lift gas into a tubing string of a well. The internal workings of valves can vary greatly, and in the present application, it is not intended to limit the valves described to any particular configuration, so long as the valve functions to regulate flow. Some of the various types of flow regulating mechanisms include, but are not limited to, ball valve configurations, needle valve configurations, gate valve configurations, and cage valve configurations. Valves can be mounted downhole in a well in many different ways, some of which include tubing conveyed mounting configurations, side-pocket mandrel configurations, or permanent mounting configurations such as mounting the valve in an enlarged tubing pod.

The term "modem" is used generically herein to refer to any communications device for transmitting and/or receiving electrical communication signals via an electrical conductor (e.g., metal). Hence, the term is not limited to the acronym for a modulator (device that converts a voice or data signal into a form that can be transmitted)/demodulator (a device that recovers an original signal after it has modulated a high frequency carrier). Also, the term "modem" as used



5 herein is not limited to conventional computer modems that convert digital signals to analog signals and vice versa (e.g., to send digital data signals over the analog Public Switched Telephone Network). For example, if a sensor outputs measurements in an analog format, then such measurements may only need to be modulated (e.g., spread spectrum modulation) and transmitted—hence no analog-to-digital conversion is needed. As another example, a  
10 relay/slave modem or communication device may only need to identify, filter, amplify, and/or retransmit a signal received.

The term “processor” is used in the present application to denote any device that is  
capable of performing arithmetic and/or logic operations. The processor may optionally include a control unit, a memory unit, and an arithmetic and logic unit.

15 The term “sensor” as used in the present application refers to any device that detects, determines, monitors, records, or otherwise senses the absolute value of or a change in a physical quantity. Sensors as described in the present application can be used to measure temperature, pressure (both absolute and differential), flow rate, seismic data, acoustic data, pH level, salinity levels, valve positions, or almost any other physical data.

20 As used in the present application, “wireless” means the absence of a conventional, insulated wire conductor e.g. extending from a downhole device to the surface. Using the tubing and/or casing as a conductor is considered “wireless.”

The term “electronics module” in the present application refers to a control device. Electronics modules can exist in many configurations and can be mounted downhole in many  
25 different ways. In one mounting configuration, the electronics module is actually located within a valve and provides control for the operation of a motor within the valve. Electronics modules can also be mounted external to any particular valve. Some electronics modules will be mounted within side pocket mandrels or enlarged tubing pockets, while others may be permanently attached to the tubing string. Electronics modules often are electrically connected  
30 to sensors and assist in relaying sensor information to the surface of the well. It is conceivable that the sensors associated with a particular electronics module may even be packaged within the electronics module. Finally, the electronics module is often closely associated with, and may actually contain, a modem for receiving, sending, and relaying communications from and to the surface of the well. Signals that are received from the surface by the electronics module are  
35 often used to effect changes within downhole controllable devices, such as valves. Signals sent or relayed to the surface by the electronics module generally contain information about downhole physical conditions supplied by the sensors.

5 In accordance with conventional terminology of oilfield practice, the descriptors "upper," "lower," "uphole," and "downhole" as used herein are relative and refer to distance along hole depth from the surface, which in deviated or horizontal wells may or may not accord with vertical elevation measured with respect to a survey datum.

The term "formation" as used in the present application refers to a bed or deposit  
10 composed throughout of substantially the same kinds of rock. A formation may or may not contain petroleum products.

Referring to FIG. 1 in the drawings, a petroleum well 10 having a wireless smart well casing 12 is illustrated. Petroleum well 10 includes a borehole 14 extending into a formation from a surface 16 to a production zone 18 that is located downhole. The casing 12 is disposed in  
15 borehole 14 and includes a structure of the type conventionally employed in the oil and gas industry. The casing 12 is typically installed in sections and is secured in borehole 14 during well completion with cement 34. A tubing string, or production tubing, 26 is generally conventional comprising a plurality of elongated tubular pipe sections joined by threaded couplings at each end of the pipe sections. Oil or gas produced by petroleum well 10 is typically  
20 delivered to surface 16 by tubing string 26.

A production platform 27 is located at surface 16 and includes a tubing hanger 28. Tubing hanger 28 supports tubing string 26 such that the tubing string 26 is concentrically positioned within casing 12. As illustrated in FIG. 1 production platform 27 also includes a gas input throttle 30 to permit the input of compressed gas into an annular space 31 between casing  
25 12 and tubing string 26. Conversely, an output valve 32 permits the expulsion of oil and gas bubbles from an interior of tubing string 26 during oil production. While FIG. 1 illustrates a gas lift well, the present invention is not so limited, and the gas input throttle valve 30 and its associated input tubing is therefore optional.

Well 10 includes a communication system 44 for providing power and two-way  
30 communication signals downhole in well 10. Casing 12 acts as an electrical conductor for communication system 44. In accordance with the present invention, an induction choke 42 is positioned concentrically around casing 12 prior to securing the casing 12 within cement 34. Induction choke 42 serves as a series impedance to electric current flow along the casing 12. The size and material of lower induction choke 42 can be altered to vary the series impedance  
35 value; however, the lower induction choke 42 is made of a ferromagnetic material. Induction choke 42 is mounted concentric and external to casing 12, and is typically hardened with epoxy to withstand rough handling.

5 A means is provided to electrically insulate casing 12 and tubing string 26 from ground connection through surface ancillary tubing connected to valves 30 and 32. Insulators 40 provide this function as shown in FIG. 1, but alternative methods exist and will be clear to those of average skill in the art, such as the use of an insulated tubing hanger (not shown) in combination with an electrical isolation tubing joint (not shown). In alternative, another  
10 induction choke (not shown) can be placed about the casing above the electrical point of connection 49 of the surface power and communication equipment 44, or two such chokes may be placed individually about the production fluids tubing and the lift gas supply pipe. As noted in the related applications, inductive chokes such as 42 external to the casing act to impede current flow on both casing and tubing at the points where these pass through such inductive  
15 chokes.

By electrically isolating a section of casing 12, power and communications signals can be supplied downhole along the casing 12 and tubing 26. While it is not an ideal electrical insulator, the cement 20 can be of low electrical conductivity and provides a degree of electrical isolation between casing 12 and the formation surrounding the well. Induction choke 42 further  
20 impedes current flow along casing 12 and tubing 26, thereby allowing the signals to be passed between induction choke 42 and the surface of the well. It is important to note that electrical contact between casing 12 and tubing string 26 does not short circuit the signals travelling along casing 12. Since tubing string 26 is also located within the annulus of induction choke 42, the choke 42 has the same electrical impedance effect on tubing string 26 as on casing 12. More  
25 specifically, current travelling down tubing string 26 is effectively blocked from travelling further downhole to a potential ground. Similar protection is provided at the top of tubing string 26 by insulating tubing joints 40. In practice the majority of the current conveyed into the well by the embodiment illustrated in FIG. 1 is carried on the casing, and the tubing contributes negligibly to the conveyance of power to depth in the well.

30 A computer and power source 44 including a power supply 46 and a spread spectrum communications device (e.g. modem) 48 is disposed outside of borehole 14 at surface 16. The computer and power source 44 is electrically connected to casing 12 at a current supply point 49 for supplying time varying current to the casing 12. Computer and power source 44 is grounded to surface 16. In operation the use of casing 12 as a conductor is lossy because of the imperfect  
35 electrical isolation provided by the cement 20. However, the spread-spectrum communications technique is tolerant of noise and low signal levels, and can operate effectively even with losses as high as -100db.

5 As shown in FIG. 1, downhole electronics module 50 is positioned proximate to an exterior surface of the casing 12 prior to completion of the well. Downhole module 50 includes a plurality of sensors 70, 72, 74, for assessing formation characteristics (i.e. physical characteristics) about the formation that surrounds the well. These sensors could include resistivity sensors, pressure sensors, temperature sensors, flow rate sensors, corrosion sensors, or  
10 geophones. Each of these sensors can be used to obtain information about the characteristics of the formation. Additionally, hydrophones could be used to measure acoustic waves in well fluids within casing 12.

It is not obvious that sensors 70 - 74 would be able to measure formation characteristics such as pressure or resistivity, since they are embedded within cement 34 and not in direct  
15 connection with formation 18. However, while the permeability of cement 34 is low, it does not provide an absolute hydraulic seal. Since the flow of formation fluids through the cement is prevented by the casing 12, the pressure of fluids in the pore spaces of the cement 34 equilibrates with the pressure in the formation. Rapid changes in formation pressure cannot be measured, but slow changes can be measured, and it is data from slow changes as the reservoir is  
20 depleted that are valuable as an indication of reservoir condition.

The same considerations apply to other physical characteristics of the formation 18, such as fluid composition, which would be reflected in resistivity changes. The interpretation of such resistivity data differs from that for a conventional resistivity log of a well as measured by open-hole logging tools. Open-hole resistivity logs reveal the spatial variation of resistivity over the  
25 logged section of the formation, measured at essentially a single instant of time. The resistivity log acquired by the methods of the present invention is derived from a locationally static single sensor, but over an extended period of time. In both cases, changes in the resistivity are the features which reveal the condition of the formation: in the open-hole log, these are spatial changes, in the present invention, the changes are a function of time rather than spatial  
30 variations.

Downhole module 50 is configured to be mechanically connected to the casing 12 either above or below induction choke 42. Electrical connections to the downhole module 50 are provided by jumpers. Power is received at the downhole module 50 by a jumper connected to casing 12 above the induction choke 42. A ground return jumper is provided that connects  
35 downhole module 50 to casing 12 below induction choke 42.

Downhole module 50 also includes a spread spectrum transceiver (not shown) for communicating with modem 48 at the surface of the well 10. The transceiver enables sensor

5 data representing the formation characteristics to be transmitted to the surface of the well 10 for use in optimizing production of the well 10. If multiple downhole modules 50 are positioned on the casing 12, the transceiver in each downhole module is able to communicate with transceivers in the other downhole modules, thereby allowing transceivers to relay signals and providing redundancy in the event of a failure of one of the downhole modules 50.

10 After positioning induction choke 42 and downhole module 50 on casing 12, the casing 12 is run into borehole 14. Cement 34 is injected into the annulus between the borehole and casing 12 to secure the casing within the borehole 14. The cement 34 also further secures the positioning of the induction choke 42 and the downhole module 50 relative to casing 12

Even though many of the examples discussed herein are applications of the present invention in petroleum wells, the present invention also can be applied to other types of wells, including but not limited to water wells and natural gas wells.

One skilled in the art will see that the present invention can be applied in many areas where there is a need to provide a communication system within a borehole, well, or any other area that is difficult to access. Also, one skilled in the art will see that the present invention can be applied in many areas where there is an already existing conductive piping structure and a need to route power and communications to a location on the piping structure. A water sprinkler system or network in a building for extinguishing fires is an example of a piping structure that may be already existing and may have a same or similar path as that desired for routing power and communications. In such case another piping structure or another portion of the same piping structure may be used as the electrical return. The steel structure of a building may also be used as a piping structure and/or electrical return for transmitting power and communications in accordance with the present invention. The steel rebar in a concrete dam or a street may be used as a piping structure and/or electrical return for transmitting power and communications in accordance with the present invention. The transmission lines and network of piping between wells or across large stretches of land may be used as a piping structure and/or electrical return for transmitting power and communications in accordance with the present invention. Surface refinery production pipe networks may be used as a piping structure and/or electrical return for transmitting power and communications in accordance with the present invention. Thus, there are numerous applications of the present invention in many different areas or fields of use.

35 It should be apparent from the foregoing that an invention having significant advantages has been provided. While the invention is shown in only a few of its forms, it is not just limited but is susceptible to various changes and modifications without departing from the spirit thereof.

5

## CLAIMS

We claim:

- 10 1. A petroleum well having a having a borehole extending into a formation and a piping structure including a casing positioned within the borehole, the petroleum well comprising:
- a downhole module positioned on the outside of the casing for collecting formation characteristic data of the formation; and
- 15 a communication system operably coupled to the piping structure and module such that the formation characteristic data can be communicated along the piping structure as a time-varying signal.
2. The petroleum well according to claim 1, wherein the downhole module includes a pressure sensor
- 20 3. The petroleum well according to claim 1, wherein the downhole module includes a flow rate sensor.
4. The petroleum well according to claim 1, wherein the downhole module includes a temperature sensor.
5. The petroleum well according to claim 1, wherein the downhole module includes a sensor for determining a resistivity value for the formation.
- 25 6. The petroleum well according to claim 1, wherein the downhole module includes a geophone for measuring acoustic waves.
7. The petroleum well according to claim 1, further comprising:
- an induction choke positioned concentrically around the piping structure; and
- 30 wherein the formation characteristic data is communicated along the piping structure between a current supply point and the induction choke.

5           8.       The petroleum well according to claim 1, further comprising:  
an upper induction choke positioned concentrically around the piping structure;  
a lower induction choke positioned concentrically around the piping structure; and  
wherein the formation characteristic data is communicated along the piping structure  
between the upper induction choke and the lower induction choke.

10

9.       In a petroleum well having a borehole extending into a formation and having a  
piping structure positioned within the borehole, a method for assessing the formation  
comprising the steps of:

15

sensing a formation characteristic of the formation using sensors external to the piping  
structure; and

communicating the formation characteristic along the piping structure as a time varying  
signal applied to the piping structure.

20

10. The method according to claim 9, wherein the communicating step further  
comprises:

providing an induction choke positioned concentrically around the piping structure; and  
communicating the formation characteristic along the piping structure between a current  
supply point and the induction choke.

25

11. The method according to claim 9, wherein the communicating step further comprises:

providing an upper induction choke positioned concentrically around the piping  
structure;

providing a lower induction choke positioned concentrically around the piping structure;  
and

30

communicating the formation characteristic along the piping structure between the upper  
induction choke and the lower induction choke.


12. The method according to claim 9, wherein the sensed formation characteristic is a  
formation fluid pressure.

---

- 5           13. The method according to claim 9, wherein the sensed formation characteristic is a formation resistivity.
14. The method according to claim 9, wherein the sensed formation characteristic is a formation fluid flow.
15. The method according to claim 9, wherein the sensed formation characteristic is a formation temperature.
- 10           16. A downhole module adapted to be coupled to an exterior surface of a piping structure comprising:  
          a sensor for sensing a physical characteristic of a petroleum formation surrounding the pipe member; and  
15           a downhole modem for transmitting the physical characteristic of the formation via a time-varying signal along the piping structure.
17. The downhole module according to claim 16, wherein the piping structure is a casing positioned within a borehole of a petroleum well.
- 20           18. The downhole module according to claim 17, wherein the physical characteristic is transmitted from the downhole modem to a surface modem at a surface of the petroleum well.
19. The downhole module according to claim 16, wherein the sensor is a pressure sensor.
20. The downhole module according to claim 16, wherein the sensor is a flow rate  
25           sensor.
21. The downhole module according to claim 16, wherein the sensor is a temperature sensor.
22. The downhole module according to claim 16, wherein the sensor is for determining a  
30           resistivity value for the formation.



- 5           23. The downhole module according to claim 16, wherein the sensor is a geophone for measuring acoustic waves.
24. The downhole module according to claim 16, wherein:  
an induction choke is concentrically positioned around the piping structure; and  
the physical characteristic of the formation is transmitted on the piping structure between  
10           a current supply point and the induction choke.
25. A method of constructing a petroleum well having piping structure including casing, comprising the steps of:  
placing the casing within the borehole of the well;  
15           embedding one or more sensors in the borehole external to the casing;  
positioning a current impedance device external to the casing; and  
providing a source of time-varying signals adapted for coupling to the piping structure of the well.
- 20           26. The method of constructing the well of claim 25, including cementing the casing in the borehole for at least a portion of thereof and embedding at least one of said sensors in the cement.
27. The method of constructing the well of claim 25, including operating the well comprising the substeps of:  
25           sensing a formation characteristic using one or more of said embedded sensors;  
communicating said sensed characteristic to a controller;  
changing an operating parameter of the well based on said formation characteristic.
28. The method of constructing the well of claim 25, including operating the well comprising the substeps of:  
30           sensing a formation characteristic using one or more of said embedded sensors;  
communicating said sensed characteristic to a surface computer as a time-varying signal along the piping structure.
-



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/06907

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B47/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 964 134 A (SCHLUMBERGER SERVICES PETROL ; SCHLUMBERGER TECHNOLOGY BV (NL); SCH) 15 December 1999 (1999-12-15)  column 1, line 41 - column 2, line 16; figures 5A, 6 column 8, line 8 - line 49	1, 2, 5-13, 16-19, 22-26
Y		20, 27, 28
X	EP 0 721 053 A (SHELL INT RESEARCH) 10 July 1996 (1996-07-10)  column 4, line 23 - line 36; figure 2 column 3, line 20 - line 23	1-4, 7-12, 14, 15
Y		20
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

19 July 2001

Date of mailing of the international search report

25/07/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Dantinne, P



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International Application No  
**PCT/US 01/06907**

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0964134	A	15-12-1999	GB 2338253 A	15-12-1999
			NO 992879 A	13-12-1999
EP 0721053	A	10-07-1996	BR 9606966 A	04-11-1997
			CA 2208661 A	11-07-1996
			DE 69600520 D	17-09-1998
			DE 69600520 T	28-01-1999
			DK 800614 T	28-06-1999
			WO 9621085 A	11-07-1996
			EP 0800614 A	15-10-1997
			NO 973088 A	02-07-1997
			RU 2149261 C	20-05-2000
			US 5745047 A	28-04-1998
WO 9937044	A	22-07-1999	AU 2067499 A	02-08-1999
			BR 9907003 A	10-10-2000
			EP 1062753 A	27-12-2000
			NO 20003638 A	08-09-2000
EP 0295178	A	14-12-1988	US 4839644 A	13-06-1989
			CA 1297163 A	10-03-1992
			DE 3853849 D	29-06-1995
			NO 173707 C	19-01-1994
WO 8000727	A	17-04-1980	EP 0020416 A	07-01-1981
			GB 2055131 A, B	25-02-1981
EP 0339825	A	02-11-1989	US 4864293 A	05-09-1989
			AU 603754 B	22-11-1990
			AU 3263389 A	02-11-1989
			DK 200789 A	30-10-1989
			JP 1315584 A	20-12-1989
US 5394141	A	28-02-1995	FR 2681461 A	19-03-1993
			CA 2078090 A, C	13-03-1993
			GB 2259832 A, B	24-03-1993
			IT 1260486 B	09-04-1996
			JP 5239985 A	17-09-1993
			NO 923540 A	15-03-1993
			OA 9595 A	30-04-1993

Rest Available Con'

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

